

| Model | TESLA MediaBox XT650 |
|--|--|
| Hardware | |
| CPU | Amlogic S905X2 Quad core ARM Cortex-A53 CPU |
| GPU | ARM Mali-G31 MP2 GPU |
| RAM | 4GB |
| ROM | 16GB |
| WiFi | Built in 2.4G/5G WiFi 2T2R Support IEEE 802.11 b/g/n/ac |
| BT | V4.2 |
| LAN Ethernet | 10/100/1000M |
| LED Displays | 4 digits LED Segment Displays and Standby :Red LED |
| Main Features | |
| OS | Android 9.0 AOSP |
| Language | English, German, French, Spanish, Italian, Chinese, Japanese etc. 24 languages |
| HDR | Dynamic HDR10, HDR10, HLG and Technicolor HDR processing |
| OTA | Support OTA update |
| I/O | 1* HDTV support 4K*2K@60 max resolution output |
| | 1* USB 2.0 |
| | 1* USB 3.0 |
| | 1* TF CARD Support 1~32GB |
| | 1* 3.5 Phone out CVBS&L/R output |
| | 1* SPDIF |
| | 1* RJ45 LAN |
| | 1* DC 12V/1A |
| DVB-T2/T | DVB-T2/T system standard: ETSI EN 302 755 |
| | Support MPLP |
| | Demodulation: QPSK, 16QAM, 64QAM or 256QAM |
| | Forward error correction rate 1/2, 2/3, 3/4, 3/5, 5/6 |
| | Guard interval : 1/4, 19/256, 1/8, 19/128, 1/16, 1/32, 1/128 |
| | Bandwidth: 6/7/8MHz |
| | Input Frange range: 54--860MHz Input Impedance: 75 Ω |
| | Input Signal level: -84 dBm to 0 dBm (average power) |
| | ANT. Connector: TV Plug 9.5mm Female |
| Video decoder | hardware decoders |
| | - VP9 Profile-2 up to 4Kx2K@60fps |
| | - H.265 HEVC MP-10@L5.1 up to 4Kx2K@60fps |
| | - AVS2-P2 Profile up to 4Kx2K@60fps |
| | - H.264 AVC HP@L5.1 up to 4Kx2K@30fps |
| | - H.264 MVC up to 1080P@60fps |
| | - MPEG-4 ASP@L5 up to 1080P@60fps (ISO-14496) |
| | - WMV/VC-1 SP/MP/AP up to 1080P@60fps |
| | - AVS-P16(AVS+) /AVS-P2 JiZhun Profile up to 1080P@60fps |
| | - MPEG-2 MP/HL up to 1080P@60fps (ISO-13818) |
| - MPEG-1 MP/HL up to 1080P@60fps (ISO-11172) | |
| - RealVideo 8/9/10 up to 1080P@60fps | |
| Decoder format | HD MPEG1/2/4, H.265/HEVC, HD AVC/VC-1, RM/RMVB, Xvid, RealVideo 8/9/10 |
| | 1* Adapter |
| | 1* Gift Box |

| | |
|--------------------|---------------------|
| Accessories | 1*IR remote control |
| | 1*HDTV Cable |
| | 1*WIFI Antenna |
| | 1*User Manual |