

MIRA Wi-Fi

Full HD Digital Satellite Receiver
 With Conax embedded card reader



- One Conax Embedded Smart Card Slot
- High Speed USB 2.0 Connection Support
- External Infra port
- TimeShifting Support
- Built in Wifi
- YouTube Support* (subject to availability)

- RSS Reader & Weather Forecast*
- MKV, AVI, MPG, MP4, TS, VOB, JPEG & MP3 Playback Support
- Software Upgrade via USB
- Dolby Digital Bit-Stream out via HDMI
- Low Power Consumption in Stand-By

* USB Wi-Fi connection required

Features and specifications are subjects to change without notice

MIRA^{Wi-Fi}

Full HD Digital Satellite Receiver
With Conax embedded card reader



TECHNICAL SPECIFICATIONS:

Tuner & Demodulation

Tuner Type:	DVB-S / DVB-S2
Input Connector:	F-type, Connector, Female
Signal Level:	-65 to -25 dBm
LNB Power:	Vertical: +13V/+13.5V, Horizontal: +18V/+18.5V
Current:	Max. 300mA Overload Protection
22K Tone Frequency:	22±1KHz
DiSeqC Control:	Version 1.0, 1.1, 1.2, USALS
Demodulation:	QPSK, 8PSK Input Symbol Rate: 2-45 Mbps, 1/2, 2/3, 3/4, 5/6, 7/8 and Auto
FEC:	

MPEG TS A/V Decoding

Transport Stream:	MPEG-2, MPEG-4 (H.264)
Input Rate:	Max. 120Mbit/s
Aspect Ratio:	4:3, 16:9, Letter Box
Video Decoding:	MPEG-2, MP@ML, MPEG-4 part 10/H264
Video Resolution:	720*480p/i, 720*576p/i, 1280*720p, 1920*1080p/i
Audio Decoding:	MPEG-1 layer I/II, MPEG-2 layer II, Dolby Digital
Audio Mode:	Left / Right / Stereo/ Mono
Sampling Rate:	32, 44.1 and 48KHz

System Resources

Main Processor:	600MHz CPU
Flash Memory:	8 MB
DDR RAM:	1024 Mbits

A/V & Data Input/Output

IR IN:	External IR Connection (Jack Type)
USB:	One USB 2.0 slot Compatible
HDMI:	VER1.4, Type A
S/PDIF:	Coaxial Digital Audio or Dolby Digital Bit Stream Output
SCART:	(1-CVBS, 1-L/R,SL,FB), or RCA output

Physical Specifications

Size[W*H*D]:	146mm*111mm*33mm
Net Weight:	0.25 Kg
Operation Temperature:	0°C~+45°C
Storage Temperature:	-10°C~+70°C
Storage Humidity:	5%~95% RH (Non-Condensing)



IR RECEIVER INCLUDED