


Λ4

SATELLITE


KODI™
You Tube
DLNA™
micro


MAIN FEATURES

- Compact Design
- One S2 satellite tuner
- One card reader
- Fast & easy installation
- 64bit Quad Core 2.0GHz processor
- 8GB integrated flash memory
- 2 USB2.0 connections
- Micro SD card expansion slot
- Google Play™
- YouTube videos
- Based on Android™
- Hundreds of thousands of available applications!
- KODI media player support
- Easy streaming to iOS, Android™ devices & PC's
- DLNA - Easy playback over local network
- 4K 2160p output via HDMI2.0
- Ethernet connection & built in Wireless-N WiFi
- Wired and wireless keyboard & mouse support
- High quality digital surround sound via S/PDIF & HDMI
- Low power consumption in Stand-By mode



TECHNICAL SPECIFICATIONS

System Resources

Main CPU:	AMlogic S905 quad core Cortex A53 64bit 2.0GHz
Main GPU:	Octo-core Mali 450MP GPU (600MHz)
RAM:	1GB DDR3
Flash Memory:	8GB

Tuner & Demodulation

Tuner Type:	DVB-S / DVB-S2
Input Connector:	F-Type (Female)
Signal Level:	-65 to -25 dBm
LNB Power:	Vertical: +13V/14V, Horizontal: +18V/19V
LNB Current:	400mA max (overload protection)
22kHz Tone:	Frequency: 22 kHz $\pm$ 4kHz
DiSEqC Control:	Version 1.0, 1.1, 1.2, USALS (Amplitude: 0.6 $\pm$ 0.2V)
Demodulation:	QPSK, 8PSK
Input Symbol Rate:	2-45Mbps, Convolution Code Rate
FEC:	1/2, 2/3, 3/4, 5/6, 7/8, 1/4, 1/3, 2/5, 3/5, 4/5, 8/9, 9/10, auto
Code Rate:	1/2, 3/5, 2/3, 3/4, 5/6

Audio / Video Decoding

Input Rate:	Max. 120Mbit/s
Aspect Ratio:	4:3, 16:9
Video Decoding:	H.265/HEVC, MPEG-2, MP@ML, MPEG-4 Part 10 / H.264
Video Resolution:	720*480p/i, 720*576p/i, 1280*720p, 1920*1080i/p, 2160p
Audio Decoding:	MPEG-1 layer I/II, Mpeg2 layer II, Dolby Digital
Audio Mode:	Left / Right / Stereo / Mono
Sampling Rate:	32, 44.1 & 48KHz

Interfaces:

HDMI:	Type-A, Version 2.0
AV:	Jack Type (CVBS video & Audio L/R output)
USB:	2x High Speed USB2.0 ports
SD Card:	1 MicroSD card slot (up to 32GB)
Ethernet:	10/100M RJ45
WiFi:	Built-in 802.11b/g/n WiFi connection
S/PDIF:	Optical for digital audio output

Power Supply:

Type:	External power supply
Input voltage:	110V - 240V AC
Output voltage:	DC 12V (2A)
Stand-By power consumption:	<0.5W

Physical Specifications:

Size (WxDxH):	140mm x 100mm x 31mm
Operation Temperature:	0°C - 40°C
Storage Temperature:	-10°C - 70°C
Storage Humidity:	5-95% RH (Non Condensing)



Features and specifications may be subjects to change without notice.