



connecting the future

TRIAX



HTS 2DC - 2 way splitter

Article number: 347012

Product description:

HTS 2DC - 2 way splitter. Low insertion loss. All ports impedance 75 Ohm. High isolation. Class A shielding - ideal for your TV system.

Specifications

ORDER INFORMATION	
EAN Number	5702663470125
SHIELDING	
Shielding effeciency VHF/UHF	> 110.0 dB
FREQUENCY	
Frequency range	5...1000 MHz
LOSS	
Insertion loss (in-out) 40-470 MHz	< 3.3 dB
Insertion loss (in-out) 470-860 MHz	< 3.9 dB

Insertion loss (in-out) 5-40 Mhz	< 3.3 dB
Insertion loss (in-out) 860-1000 MHz	< 4.1 dB
ISOLATION	
Isolation (tap-tap) 40-470 MHz	> 28.0 dB
Isolation (tap-tap) 470-860 MHz	> 25.0 dB
Isolation (tap-tap) 5-40 MHz	> 28.0 dB
Isolation (tap-tap) 860-1000 MHz	> 25.0 dB
RETURN LOSS	
Return loss (in-out) 40-470 MHz	> 22.0 / > 22.0 dB
Return loss (in-out) 470-860 MHz	> 20.0 / > 20.0 dB
Return loss (in-out) 5-40 MHz	> 24.0 / > 24.0 dB
Return loss (in-out) 860-1000 MHz	> 20.0 / > 20.0 dB
ELECTRICAL	
Impedance	75 Ω
OPERATIONAL	
Certification	CE
DC Passthrough	Yes
CONNECTORS	
Connector Type	F-female
Number of outputs	2
MECHANICAL	
Product Depth	16 mm
Packaging Depth	0,050 m
Packaging Height	0,020 m
Total Weight	0,051 kg
Packaging Width	0,050 m
Net Weight	0,045 kg

Packing QTY	1
Tara Weight	0,006 kg
Weight (kg)	0 kg
Product Width	52 mm
Product Height	50 mm
