


TRIAx



FREQUENCY	
Frequency range	5...2400 MHz
LOSS	
Insertion loss (in-out) 2150-2400 Mhz	10.5 dB
Insertion loss (in-out) 40-1000 Mhz	7.5 dB
Insertion loss (in-out) 5-40 Mhz	6.5 dB
Insertion loss (in-out) 1000-2150 MHz	10.0 dB
ISOLATION	
Isolation (tap-tap) 1000-2150 MHz	23 dB
Isolation (tap-tap) 2150-2400 MHz	23 dB
Isolation (tap-tap) 40-1000 MHz	22 dB
Isolation (tap-tap) 5-40 MHz	23 dB
RETURN LOSS	
Return loss (in-out) 1000-2150 MHz	13.0 dB
Return loss (in-out) 2150-2400 MHz	13.0 dB
Return loss (in-out) 40-1000 MHz	12.0 dB
Return loss (in-out) 5-40 MHz	10.0 dB
ELECTRICAL	
Impedance	75 Ω
OPERATIONAL	
Certification	CE, RoHS II
DC Passthrough	Yes (max. 500mA)
Screening Efficiency	EN50117 (Class A)
CONNECTORS	
Connector Type	F-female
Number of outputs	3

MECHANICAL	
Product Depth	16 mm
Packaging Depth	0,075 m
Packaging Height	0,018 m
Total Weight	0,058 kg
Packaging Width	0,055 m
Net Weight	0,058 kg
Packing QTY	1
Product Width	74 mm
Product Height	56 mm
Bracket (optional)	2x BS / Art No 342100